

Diesel Heater

Efficient Heating for Every Explorer



Bluetooth Control

App-Controlled Heating



LCD Panel & Remote

Easy Adjustment



3 Operating Modes

Fan, Manual, Smart



Quiet Operation

Low-Noise Performance



Quick Heat-Up

Fast Warm-Up



Easy Installation

DIY Installation



Safety Features

High/Low Voltage Protection



RCM Certified

Designed for Australian Conditions



BORN TO ROAM 2KW Bluetooth Diesel Heater Kit

(WITH 5L TANK)

Featuring **Bluetooth** connectivity for easy smartphone control, this heater lets you manage your warmth with just a tap.

The user-friendly **LCD panel** and **Remote** offer three modes—fan only, manual heat, and smart mode—ensuring personalised comfort.

Installation is a breeze with a specially designed mounting plate and detachable pump power.

Safety is built-in, with high and low voltage protection, plus an auto cool-down feature for peace of mind.

A **5L** stainless steel fuel tank and ultra-quiet pump ensure reliable, uninterrupted heating.

RCM certified and packed with everything you need, this heater is ready for the Australian outdoors.



BORN TO ROAM Diesel Heater Kit Proudly
Distributed in Australia & New Zealand By





Diesel Heater KIT





PRODUCT SPECIFICATIONS

	·
POWER	Adjustable 1KW-2KW
FUEL	Diesel Only
RATED VOLTAGE	DC 12V
FUEL CONSUMPTION	0.1-0.3 L/h
WORKING TEMPERATURE	-40°C to +50°C
OIL PUMP WORKING TEMPERATURE	-40°C to +40°C
MAIN UNIT DIMENSIONS	340mm (L) x 115mm (H) x 115mm (W)
TANK DIMENSIONS	110mm (D) x 325mm (H) x 265mm (W) with 70mm Neck & Cap Height
CASING	Black Flame-Retardant Plastic
LCD DISPLAY	Easy Read Out and Troubleshooting
POWER CONSUMPTION	5-35w/h, Peak Up to 90-150w During Glow Plug Heating

Adventure in Comfort Efficient Heating for Every Explorer

MAIN BODY

Solid construction. Japanese KYOCERA glow plug. Quiet motor. Balanced fan. 3 wire temperature sensor. High end wiring harness adaptor. Sealed quality ECU.

HARNESS UNIT

Power cable L5M Spec 2.5mm². Includes Anderson plugs. All wiring with conduit protection. Waterproof fuse.

FUEL UNIT

Hard Nylon fuel line (7.8mpa/120*c). Reusable fuel filter. 304 grade stainless steel fuel tank with lockable cap and fuel gauge. Quiet pump.

INSIDE AIR UNIT

1.5m ducting with clamps. 2 x flat directional vents.

EXHAUST UNIT

600 mm exhaust pipe with heat-resistant sleeve. High-quality baffled muffler 100 mm exhaust tip. Heavy-duty exhaust clamps & P-clamps to provide additional support to the exhaust.

OUTSIDE

High quality exhaust system. High quality air filter. Heavy duty clamps.

LCD & REMOTE

Premium LCD control panel with remote control. Bluetooth mobile app is available. Adjustable thermostat sensor reading.





